


# 2P 系列二位二通电磁阀

## series 2/2-way solenoid valve



### 图形符号 Graphical symbols



### 产品特点 Features

采用直动式、快速反应、可多用途使用、高效率、长寿命、优良的防水性能。

Direct drive type, quick feedback, multi application, long performance life, excellent waterproof.

### 型号注释 Note for type

2P 025 - 06 - AC220V - W

规格代码 2p: 二位三通电磁阀(塑钢型)	Specification 2P:2 position 3 way solenoid valve(Reinforced plastic Steel type)
流量孔径 025: 2.5mm	Aperture of Flow Rate 025: 2.5mm
接管口径 06:1/8", 08:1/4"	Joint Pipe Bore: 06:1/8", 08:1/4"
标准电压 Standard Voltage: DC12V, DC24V, AC24V 50Hz/60Hz, AC110V 50Hz/60Hz, AC220V 50Hz/60Hz, AC380V 50Hz/60Hz	
空白: 接线形式 LD: 标准端子式 LD <sub>1</sub> : 棕色带灯端子式 LD <sub>2</sub> : 白色带灯端子式 W: 引线式	Wiring Form Blank: standard connector Brown with lighting connector White with lighting connector Lead wire type

### 规格 Specification

型号 Model	3V1-M5	3V1-06
工作介质 Working Medium	空气、水、油、瓦斯/Air, Water, Oil, Gas	
动作方式 Motion pattern	直动式 / Direct Drive Type	
型式 Type	常闭型/Normal Close Type	
流量孔径 Aperture of Flow Rate	2.5	
CV值 CV Value	0.23	
接口口径 Joint Pipe Bore	1/8"	1/4"
使用流体粘滞度 Operation Fluid Viscosity	20 CST以下 (Below)	
使用压力 Working pressure	0-0.7MPa	
最大耐压力 Max. Pressure Resistance	1.0MPa	
工作温度 Operatong Temperature	-5~80	
使用电压范围 Voltage Range	±10%	
本体材质 Material of Body	工程塑料 / Engineering Plastic	
油封材质 Material Oil Seal	NBR或VITON / NBR or VITON	

### 外形尺寸 Outlook & Dimension

