

2W 系列二位三通直动式电磁阀

series 2/2-way direct drive type solenoid valve

2W 二位三通直动式电磁阀

2/2-way Direct Drive Type Solenoid Valves



图形符号 Graphical symbols



产品特点 Features

采用膜片密封结构，动作灵敏，流量大，结构简单，维修容易，优良的防水性能。

With diaphragm seal, quick feedback, high flow, simple structure, easy of maintenance, excellent waterproof.

型号注释 Note for type

2W 025 - 08 AC110V - E

规格代码 2W: 二位三通电磁阀-直动式 2WH: 二位三通电磁阀-直动式(高压型)	Specification 2/2- way Solenoid valve--Direct Drive Type 2/2- way Solenoid valve-Direct Drive Type(High pressure Type)
2S: 不锈钢二位三通电磁阀-直动式 2SH: 二位三通电磁阀-直动式(高压型)	Stainless Steel 2/2- way Solenoid valve--Direct Drive Type Stainless Steel 2/2- way Solenoid valve--Direct Drive Type(High pressure Type)
流量孔径 Aperture of Flow Rate	012: 1.2mm, 020: 2mm, 025: 2.5mm, 040: 4mm
接管口径 Joint Pipe Bore:	06: 1/8", 08: 1/4", 10: 3/8"
标准电压 Standard Voltage: DC12V, DC24V, AC24V 50Hz/60Hz, AC110V 50Hz/60Hz, AC220V 50Hz/60Hz, AC380V 50Hz/60Hz	
油封代号 空白: NBR E: EPDM(蒸汽用) V: VITON(高温、瓦斯及真空用)	Oil Seal Code NBR EPDM (for steam) VITON (for high temperature gas and vacuum)

技术参数 Specification

型号 Model	2W025-06	2W025-08	2W040-10	2WH012-06	2WH012-08	2WH020-10
	2S025-06	2S025-08	2S040-10	2SH012-06	2SH012-08	2SH020-10
工作介质 Working Medium	空气、水、油、瓦斯/Air, Water, Oil, gas					
动作方式 Motion pattern	直动式 / Direct Drive Type					
型式 Type	常闭型 / Normal Close Type					
流量孔径 Aperture of Flow Rate	2.5		4	1.2		2
CV值 CV Value	.23		.60	0.05		0.15
接管口径 Joint Pipe Bore	1/8"	1/4"	3/8"	1/8"	1/4"	3/8"
使用流体粘滞度 Operation Fluid Viscosity	20 CST以下 (Below)					
使用压力 Working pressure	空气、水、油、瓦斯/Air, Water, Oil, gas: 0~0.7			空气、水、油/Air, Water, Oil: 0~0.7, 0.1~1.5		
最大耐压力 Max. Pressure Resistance	1.0			3.5		
工作温度 Operation Temperature	-5~80					
使用电压范围 Voltage Range	±10%					
本体材质 Material of Body	2W: 黄铜 Brass			2S: 不锈钢: Stainless Steel		
油封材质 Material of Oil Seal	NBR, EPDM 或 VITON / NBR, EPDM or VITON					